

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
2.40"	ITLT0240QVCF25UM Integrated 4 Wire RTP	TTL	QVGA 240x320 3:4 Normally White, Transmissive	420	18 Bit	80/80/70/80	12 O'Clock	-20~70 -30~80	42.70 x 59.45 x 3.98 36.72 x 48.96
2.40"	ITLT0240QVCN23UM	TTL	QVGA 240x320 3:4 Normally White, Transmissive	500	18 Bit	80/80/70/80	12 O'Clock	-20~70 -30~80	42.70 x 59.45 x 3.00 36.72 x 48.96
3.50"	ITLT0350QVRN11CM	TTL	QVGA 320x240 4:3 Normally White, Transmissive	300	24 Bit	60/60/50/55	6 O'Clock	-20~70 -30~80	76.90 x 63.90 x 3.26 90.08 x 52.56
3.50"	ITLT0350QVRF22AM Integrated 4 Wire RTP	TTL	QVGA 320x240 4:3 Normally White, Transmissive	320	24 Bit	60/60/50/55	6 O'Clock	-20~70 -30~80	76.90 x 63.90 x 4.40 70.08 x 52.56
4.30"	ITLT0430WQRF26CM Integrated 4 Wire RTP	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	400	24 Bit	70/70/50/70	12 O'Clock	-20~70 -30~80	105.50 x 67.20 x 4.05 95.04 x 53.86
4.30"	ITLT0430WQRN25CH	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	500	24 Bit	70/70/50/70	12 O'Clock	-20~70 -30~80	105.50 x 67.20 x 2.90 95.04 x 53.86
4.30"	ITLT0430WQRF64ZH_A3 Integrated 4 Wire RTP	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	700	24 Bit	75/75/55/75	6 O'Clock	-20~70 -30~80	105.40 x 67.10 x 3.90 95.04 x 53.85
5.00"	ITLT0500WVRF52WM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	300	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.00 x 4.65 108.00 x 64.80
5.00"	ITLT0500WVRP55WM Integrated PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	300	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.00 x 4.10 108.00 x 64.80
5.00"	ITLT0500WVRF54WH Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	700	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.90 x 6.43 108.00 x 64.80
5.00"	ITLT0500WVRN53WH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	800	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.90 x 4.83 108.00 x 64.80
5.60"	ITLT0560VGRF23CM Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	160	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	126.50 x 100.00 x 7.25 112.90 x 84.67
5.60"	ITLT0560VGRF23CM_A1 Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	160	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	126.50 x 100.00 x 7.25 112.90 x 84.67
5.70"	ITLT0570QVRF33ZM Integrated 4 Wire RTP	TTL	QVGA 320x240 4:3 Normally White, Transmissive	400	18 Bit	80/80/70/80	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 13.80 115.20 x 86.40
5.70"	ITLT0570VGRF23ZH_A3 Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	560	18 Bit	80/80/70/70	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 13.80 115.20 x 86.40
5.70"	ITLT0570QVRN34ZH_A1	TTL	QVGA 240x320 3:4 Normally White, Transmissive	1200	18 Bit	80/80/70/70	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 12.30 115.20 x 86.40

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
7.00"	ITLT0700SWLN42CM	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	250	24 Bit	75/75/70/75	6 O'Clock	-20~60 -30~70	165.75 x 105.39 x 3.40 153.60 x 90.00
7.00"	ITLT0700SWLP47CM_A3 Integrated PCAP	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	250	24 Bit	85/85/85/85	6 O'Clock	-20~60 -30~70	184.00 x 121.00 x 4.90 153.60 x 90.00
7.00"	ITLT0700SWLF43CL Integrated 4 Wire RTP	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	280	24 Bit	75/75/70/75	6 O'Clock	-20~60 -30~70	165.70 x 105.40 x 4.92 153.60 x 90.00
7.00"	ITLT0700WVRF34CL Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	280	18 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	165.00 x 104.44 x 6.75 152.40 x 91.44
7.00"	ITLT0700WVRF16ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	320	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90x 100.00 x 7.25 154.08 x 85.92
7.00"	ITLT0700WVRF24CM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	320	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 7.25 154.08 x 85.92
7.00"	ITLP0700WXLP64TM Integrated PCAP	LVDS	WXGA 1280x800 16:9 IPS Normally Black, Transmissive	350	24 Bit	89/89/89/89	Free IPS	-20~60 -30~70	161.00 x 107.00 x 5.35 149.76 x 93.6
7.00"	ITLT0700WVRN32CM_A2	TTL	WVGA 800x480 16:9 Normally White, Transmissive	350	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.44 x 5.20 152.40 x 91.44
7.00"	ITLT0700WVRP38CM_A4 Integrated PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	350	18 Bit	70/70/60/70	6 O'Clock	-20~60 -30~70	185.40 x 116.80 x 7.00 152.40 x 90.80
7.00"	ITLT0700SVRF04ZM Integrated 4 Wire RTP	TTL	SVGA 800x600 4:3 Normally White, Transmissive	380	18 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	154.00 x 119.20 x 7.90 141.60 x 106.20
7.00"	ITLT0700WVLF26CM Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	400	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 10.25 154.08 x 85.92
7.00"	ITLT0700WVLF34ZM Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	400	18 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	165.00 x 104.44 x 6.73 152.40 x 91.44
7.00"	ITLT0700WVLN25CM	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	400	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 8.70 154.08 x 85.92
7.00"	ITLT0700WVRF54ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	400	24 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	165.00 x 104.44 x 6.73 152.4 X 91.44
7.00"	ITLT0700WVRP38CH_A1 Integrated PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	800	18 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	180.00 x 110.00 x 6.70 152.40 x 91.44
7.00"	ITLT0700WVLN27ZH	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 8.70 154.08 x 85.92

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
7.00"	ITLT0700WVRN16CH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	1000	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	164.90 x 100.00 x 3.35 154.08 x 85.92
7.00"	ITLT0700WVRN36CH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.44 x 5.20 152.40 x 91.44
7.00"	ITLT0700SWLPA4CM Integrated PCAP	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	1500	24 Bit	75/75/65/75	6 O'Clock	-20~60 -30~70	184.00 x 121.00 x 7.10 153.60 x 90.00
8.00"	ITLT0800WVLF75ZM Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	360	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	192.80 x 116.90 x 8.01 x 11. 176.64 x 99.36
8.00"	ITLT0800WVRF62ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	360	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	192.80 x 116.90 x 8.01 176.64 x 99.36
8.40"	ITLT0840SVLF46GM_A5 Integrated 4 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	350	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 9.55 170.40 x 127.80
8.40"	ITLT0840SVLN45GM_A3	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	400	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 8.00 170.40 x 127.80
8.40"	ITLT0840SVLF56GH Integrated 4 Wire RTP	TTL	SVGA 800x600 4:3 Normally White, Transmissive	800	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 9.55 170.40 x 127.80
9.70"	ITLP0970XGLN12CM A5_	LVDS	XGA 1024x768 4:3 IPS Normally Black, Transmissive	380	24 Bit	89/89/89/89	Free IPS	-25~70 -25~70	210.20 x 164.00 x 5.12 197.00 x 147.00
10.10'	ITLP1010WXLF12CM_A1 Integrated 4 Wire RTP	LVDS	WXGA 1280x800 16:9 MVA Normally Black, Transmissive	350	24 Bit	85/85/85/85	Free MVA	-20~60 -30~70	229.46 x 149.10 x 4.25 216.96 x 135.60
10.10'	ITLP1010WXLP15CM_A1 Integrated PCAP	LVDS	WXGA 1280x800 16:9 MVA Normally Black, Transmissive	420	24 Bit	85/85/85/85	Free IPS	-20~70 -30~80	257.00 x 157.00 x 5.40 216.96 x 135.60
10.20'	ITLT1020WVRF45ZM_A4 Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9	280	24 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	235.00 x 145.80 x 11.90 222.00x 132.48
10.40'	ITLT1040XGLF45TM_A2 Integrated 4 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	300	18 Bit	70/70/65/55	6 O'Clock	-20~70 -30~80	236.00 x 174.30 x 9.00 211.20 x 158.40
10.40'	ITLT1040XGLP47TM_A1 Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	320	18 Bit	70/70/65/55	6 O'Clock	-20~70 -30~80	239.10 x 186.30 x 9.77 211.20 x 158.40
10.40'	ITLT1040SVLN31TM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	400	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 5.60 211.20 x 158.40
10.40'	ITLT1040XGLN42TM	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	400	18 Bit	70/70/65/55	6 O'Clock	-30~80 -20~70	236.00 x 174.30 x 7.40 211.20 x 158.40

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
10.40'	ITLT1040XGLV44TM Integrated 5 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	400	18 Bit	70/70/65/55	6 O'Clock	-30~80 -20~70	236.00 x 174.30 x 9.80 211.20 x 158.40
10.40'	ITLT1040XGLP48TH Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1000	18 Bit	70/70/65/55	6 O'Clock	-30~80 -30~80	259.10 x 206.30 x 10.10 211.20 x 158.40
12.10'	ITLV1210WXLP46CM Integrated PCAP	LVDS	WXGA 1280x800 16:9 MVA Normally Black, Transmissive	320	24 Bit	85/85/85/85	Free MVA	-27~70 -30~80	302.90 x 204.40 x 12.83 261.12 x 163.20
12.10'	ITLT1201SVLF46ZM Integrated 4 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	360	24 Bit	80/80/75/65	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 10.55 246.00 x 184.50
12.10'	ITLT1210WXLN42CM	LVDS	WXGA 1280x800 16:9 Normally Black, Transmissive	400	24 Bit	85/85/85/85	6 O'Clock	-10~70 -20~80	278.00 x 184.00 x 8.16 261.12 x 163.20
12.10'	ITLT1210XGLV17ZM Integrated 5 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	400	24 Bit	80/80/60/80	6 O'Clock	-30~85 -30~85	279.00 x 209.00 x 9.00 245.76 x 184.32
12.10'	ITLT1210XGLN13AM	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	500	24 Bit	80/80/60/80	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 9.00 245.76 x 184.32
12.10'	ITLT1210XGLN17GH	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1000	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 9.00 245.76 x 184.32
12.10'	ITLT1210XGLP18GE Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1500	24 Bit	80/80/60/80	6 O'Clock	-30~85 -30~85	287.67 x 226.20 x 11.42 245.76 x 184.32
15.00'	ITLT1500XGLP16CL Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	200	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	339.10 x 262.15 x 14.60 303.00 x 228.00
15.00'	ITLT1500XGLV15CL Integrated 5 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	200	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	339.10 x 262.15 x 14.20 303.00 x 228.00
15.00'	ITLT1500XGLN12CL	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	250	24 Bit	80/80/70/70	6 O'Clock	-30~80 -40~85	326.50 x 235.30 x 11.80 304.10 x 228.10
15.00'	ITLT1500XGLN17BE	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1500	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	326.00 x 255.00 x 11.80 304.10 x 228.10
15.00'	ITLT1500XGLP18BE Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1500	24 Bit	80/80/70/80	6 O'Clock	-30~80 -30~80	358.60 x 273.06 x 13.50 303.00 x 228.10
15.60'	ITLT1560WXLN31AL	LVDS	XGA 1366x768 16:9 Normally White, Transmissive	300	24 Bit	85/85/80/80	6 O'Clock	-10~50 -20~60	363.80 x 215.90 x 16.85 344.20 x 193.50
15.60'	ITLT1560WXLN32AM	LVDS	XGA 1366x768 16:9 Normally White, Transmissive	420	24 Bit	85/85/80/80	6 O'Clock	-10~50 -20~60	363.80 x 215.90 x 16.85 344.20 x 193.50

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
17.00'	ITLT1700SXLN34GH_A1	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	1200	24 Bit	85/85/50/80	6 O'Clock	-30~85 -30~85	358.50 x 296.50 x 18.00 337.92 x 270.34
18.50'	ITLT1850HDLP23GM Integrated PCAP	LVDS	WXGA 1366x768 16:9 Normally White, Transmissive	240	24 Bit	85/85/80/80	6 O'Clock	-20~60 -20~50	445.00 x 265.60 x 19.22 409.80 x 230.40
18.50'	ITLT1850HDLP25GH Integrated PCAP	LVDS	WXGA 1366x768 16:9 Normally White, Transmissive	800	24 Bit	85/85/80/80	6 O'Clock	-20~60 -20~50	445.00 x 265.60 x 19.22 409.80 x 230.40
19.00'	ITLT1900SXLN41AM	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	350	24 Bit	88/88/85/85	6 O'Clock	-0~50 -20~60	396.00 x 324.00 x 17.80 376.30 x 301.10
19.00'	ITLT1900SXLN44BE	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	1200	24 Bit	88/88/80/85	6 O'Clock	-20~70 -30~80	396.00 x 324.00 x 17.80 376.30 x 301.10
21.50'	ITLV2150HDLV34BH Integrated 5 Wire RTP	LVDS	WUXGA 1920x1080 16:9 IP Normally Black, Transmissive	1000	24 Bit	89/89/89/89	Free IPS	-20~70 -30~80	496.50 x 292.20 x 13.02 476.64 x 268.11
21.50'	ITLV2150HDLN33BH	LVDS	HD 1920x1080 Normally Black, Transmissive	1200	24 Bit	89/89/89/89	Free MVA	-20~70 -30~70	495.60 x 292.20 x 10.50 476.64 x 268.11